

# **CLASSIC CRACKMATE**

# **Polymer Based Crack Filling Powder**

# **PRODUCT**

A factory blended easy-to-use, polymer modified, high strength, non-shrink, cementitious crack filling mortar. Designed for cost effective filling of cracks in concrete, masonry and plaster surfaces, including shrinkage cracks in plaster.

# **ADVANTAGES & BENEFITS**

- Non-shrink mortar with strong adhesive properties.
- Excellent crack filling ability
- \* Smooth finish
- \* Prevents further crack propagation
- \* High tensile strength

# **DESCRIPTION**

*Classic Crackmate* is a polymer modified cementitious crack filling mortar with non-shrink properties, prepared by adding the specified quantity of water to the powder.

*Classic Crackmate* is used to fill cracks in both interior and exterior concrete, masonry and plaster surfaces. It can also be used as a thin render to even out surfaces.

# **PACK & COVERAGE**

0.5 & 1 kg packs.

1 kg will fill approx. 30 – 40 m length of cracks cut into 6 mm deep V-groove.

# **INSTRUCTIONS FOR USE**

# Surface Preparation

Cut the cracks into 6 mm deep V-grooves. Clean the grooves with a wire brush to remove all loose particles. Sprinkle grooves with clean water.

# **Mixing**

**Classic Crackmate** should be preferably mixed mechanically using a slow speed drill with paddle attachment, slowly adding 1 kg of **Classic Crackmate** to 250 to 300 ML of clean water, until a homogenous mortar of smooth, creamy and trowellable consistency is obtained.

# **Application**

Fill the prepared cracks tightly with the mortar using a small trowel or putty blade and finish to a level surface. Remove excess mortar with clean moist sponge or soft cloth before it dries totally.

#### HANDLING PRECAUTIONS

*Classic Crackmate* is non-toxic, but mildly alkaline when wet. However, in its wet state, if contact with skin occurs, wash well with clean water. Inhalation of dust from the dry material should be avoided.

# STORAGE LIFE

*Classic Crackmate* has a shelf life of 6 months when stored, unopened in the original pack, under dry condition at moderate temperatures.

# **OUR RANGE INCLUDES**

- Admixture
- Waterproofing
- Sealants & Protective Coating
- Repairs, Adhesives and Surface Treatment
- Industrial Grout & Flooring
- Epoxy Products

#### ECO FRIENDLY & SPECIAL PRODUCTS

- Liquid Granites
- Geo Polymer based Eco Friendly Products



PRIMADON CONSTRUCTION PRODUCTS PVT. LTD.

F-C2, Sri Sai Raj Apartments, Indian Airlines Colony, Trimulgherry, Secunderabad - 500015, AP, India.