



# CLASSIC PRIME COAT

## Polymeric Cementitious Prime Coating

---

### **PRODUCT:**

*Classic Primecoat* is a two pack polymeric cementitious system, primary protective coat for concrete. Provides a thin section coat with good bonding between old and new surfaces.

### **ADVANTAGES:**

- \* Easy to apply
- \* Pre-packed
- \* Excellent weather resistance
- \* Excellent bonding
- \* Contains no corrosive substances

### **COVERAGE**

A 2kg pack will cover approximately 7 m<sup>2</sup> area.

### **USES:**

All concrete surfaces where bonding is required.

### **PACK:**

2 kg, 1 kg packing

### **TYPICAL PROPERTIES:**

Working life at 20°C -	30 minutes
Touch dry time at 20°C -	4 hours

### ***DESCRIPTION***

***Classic Primecoat*** is a thin section polymeric coat designed to provide an excellent bond between old and new surfaces.

### ***INSTRUCTIONS FOR APPLYING CEMPATCH PRIMER***

#### ***Surface Preparation:***

The concrete should be cleaned with wire brush or acid cleaning. All dust particles should be removed to achieve good bonding of coating.

#### ***Mixing:***

***Classic Primecoat*** is supplied in two pack system with a powder component and the respective pre-weighed amount of liquid. The liquid should be poured into the suitable mixing vessel and the powder component gradually added under mechanical mixing. The continuous mixing should be done until a homogeneous colour is achieved.

#### ***Application:***

One coat of mixed ***Classic Primecoat*** should be applied by brush on substrate

#### ***STORAGE LIFE:***

Atleast one year in manufacturer's undamaged, sealed containers, when stored in dry, frost-free conditions.



PRIMADON CONSTRUCTION PRODUCTS PVT. LTD.  
F-C2, Sri Sai Raj Apartments, Indian Airlines Colony, Trimulgherry,  
Secunderabad - 500015, AP, India.