



# CLASSIC TA

## High Performance Ceramic Tile Adhesive

### **DESCRIPTION**

**Classic TA** can be used in totally submerged conditions. Good open wet time for improved workability.

### **USES**

**Classic TA** is a high quality adhesive for the permanent fixing of ceramic tiles. It can also be used for fixing of insulating and acoustic boards. Tiled surfaces after curing can be used for damp and submerged services like toilets and swimming pools.

### **INSTRUCTIONS FOR USE**

#### **Surface Preparation**

All surfaces must be sound and thoroughly cleaned before **Classic TA** is applied. All traces of grease or oil must be removed with suitable degreaser. All loose particles of mortar and paints must be physically removed.

#### **Mixing**

**Classic TA** should be mixed with water in the ratio of 3:1 by volume. Water can be reduced or increased slightly to increase required consistency. Powder to be added slowly to the water and not water to powder.

#### **Application**

**Classic TA** can be applied directly on concrete, cement screeds, cement lime mortars.

#### **Finishing**

Remove excess adhesive with a damp cloth before material has set. Joint grouting may be commenced 24 hrs. after tiles have been laid, with **Classic TP** joint filler.

### **COVERAGE**

**Classic TA** is spread on the substrate to a uniform thickness of 3 to 5 mm. Choose work areas so that they can be tiled in adhesive open wet time approximately 30 mins at a 30°C. 25 kg pack of **Classic TA** covers approximately 4 sq.m. at 3 mm thickness.

### **PACK**

25 kg

### **HANDLING PRECAUTIONS**

**Classic TA** is non-toxic. However, splashes on the skin should be washed well with water and if contact with eye occurs wash well with water and seek medical advice.



PRIMADON CONSTRUCTION PRODUCTS PVT. LTD.  
F-C2, Sri Sai Raj Apartments, Indian Airlines Colony, Trimulgherry,  
Secunderabad - 500015, AP, India.