

CLASSIC TT

High Performance Single Component Tile on Tile Adhesive

DESCRIPTION

Classic TT has good flexibility – can resist thermal movement. It can be used for external cladding of tiles and granite stones. It has good bonding even on smooth surface with excellent waterproofing properties.

USES

Classic TT is a high quality adhesive single component for the permanent fixing of tiles, stones and granite including tile on tile. It can also be used for fixing of insulating and acoustic boards. Tiled surfaces after curing can be used for damp and submerged services like toilets and swimming pools.

INSTRUCTIONS FOR USE

Surface Preparation

All surfaces must be sound and thoroughly cleaned before *Classic TT* is applied. All traces of grease or oil must be removed with suitable degreaser. All loose particles of mortar and paints must be physically removed.

Mixing

Mix 3 to 3.5 parts of *Classic TT* into 1 part of potable water by volume and mix into a creamy consistency. Water can be reduced or increased slightly to achieve required consistency.

A slow speed drill fitted with a suitable mixing paddle is recommended. Hand mixing may also be resorted if drill/paddle is not available. Powder to be added slowly to the water and not water to powder.

Application

Classic TT can be applied directly on concrete, cement screeds, cement lime mortar and tiles. It can bond well even on smooth surface.

Finishing

Remove excess adhesive with a damp cloth before material has set. Joint grouting may be commenced 24 hours after tiles have been laid, with *Classic TP* joint filler.

COVERAGE

Classic TT is spread behind the tile to a uniform thickness of 3 to 5 mm. It covers approximately 5 sq.m. at a thickness of 3 mm per 25 kg pack.

PACK

5 kg and 25 kg

HANDLING PRECAUTIONS

Classic TT is non-toxic. However, splashes on the skin should be washed well with water and if contact with eye occurs wash well with water and seek medical advice.

