



CLASSIC WALL PUTTY

Polymer Modified fibre reinforced Wall Putty

PRODUCT

A polymer modified and fibre-reinforced cementitious wall putty in powder form, which on mixing with water, can be easily applied in thin coats with a putty knife. Used as a thin plaster or skim coat to provide a level and very smooth surface for painting. Replaces conventional and enamel putty.

DESCRIPTION

Classic Wallputty is a white coloured polymer modified and fibre-reinforced cementitious wall putty in powder form, which on mixing with requisite water forms a paste that can be applied in thin coats with a putty knife.

Classic Wallputty has got better adhesion and flexural properties. Due to its better water retention properties, the mixed paste has got increased life and workability. **Classic Wallputty** finished surface is also resistant to shrinkage and cracking even when applied in thin coats.

Classic Wallputty is applied as a thin plaster or skim coat on walls & ceilings to provide a level and very smooth surface for subsequent painting or wall papering. It can be used on both interiors & exteriors over plastered surfaces concrete and block work. It should not be applied over painted surfaces. It resists water absorption, but permits breathing of water vapour, which is important for concrete surfaces.

ADVANTAGES

- * Good adhesion
- * Cracks & shrinkage suppressed
- * Better workability
- * Increased flexural strength
- * Low water absorption
- * Permits breathing
- * Ease of application

PACK & COVERAGE

5 Kg, 25 kg Bag.

1 kg covers 2 to 3 Sq.m Coverage varies accordingly to the surface finish.

PROPERTIES

Working Time : 2 to 3 hours

Bond strength to concrete: 0.8 N/mm²

INSTRUCTIONS FOR USE

Classic Wallputty should be mixed with a slow-speed drill and paddle by adding the contents of a 20 kg bag to 6 to 7.5 litres of clean water to obtain the required consistency. The resultant paste is applied with a putty knife over clean surfaces free from dust, oil, laitance, paint, etc. It is applied to a thickness of 1 to 3 mm to provide a level and very smooth surface. The usage works out to 2 to 3 kg/m² for an average 2 to 3 mm mm-thick application. Once the surface has hardened it can be painted or wall papered.

STORAGE LIFE

Minimum six months, when stored under dry conditions in original sealed packs.

HANDLING PRECAUTIONS

Classic Wallputty is nontoxic, but mildly alkaline when wet. If the skin comes into contact with the material, it should be washed with clean water. Eyes should also be washed with copious quantities of clean water in case of contact. Inhalation of dust from dry material should be avoided.

OUR RANGE INCLUDES

- **Admixture**
- **Waterproofing**
- **Sealants & Protective Coating**
- **Repairs, Adhesives and Surface Treatment**
- **Industrial Grout & Flooring**
- **Epoxy Products**

ECO FRIENDLY & SPECIAL PRODUCTS

- **Liquid Granites**
- **Geo Polymer based Eco Friendly Products**



PRIMADON CONSTRUCTION PRODUCTS PVT. LTD.
F-C2, Sri Sai Raj Apartments, Indian Airlines Colony, Trimulgherry,
Secunderabad - 500015, AP, India.