



# CLASSIC ACRYSEAL

## Single Part Acrylic Sealant

### DESCRIPTION

**Classic Acryseal** is a Single part, general purpose acrylic sealant which can be used internally and externally. It cures on exposure to the atmosphere to form a flexible sealant. **Classic Acryseal** does not require any primer. It may be used directly on the cracks and joints.

### ADVANTAGES & BENEFITS

- Single component ready for use.
- 10% movement accommodation factor.
- UV resistant.
- Excellent adhesion to most building substrates.
- Can be painted.
- Available in a wide range of colors.

### METHOD OF USE

#### Joint Surface Preparation

Surface must be clean, dry and free from dust, grease, oils and all other contaminants.

#### Joint Backing

Where applicable, appropriate joint backing rod such as closed cell polyethylene foam, should be used to provide the correct joint depth.

#### Normal Application

**Classic Acryseal** is supplied in pre-packed package. It will be used by normal putty plate to cover the prepared cracks or joints.

#### Cartridges Application

**Classic Acryseal** is supplied in cartridges and can be applied into the joint using a skeleton gun. Cut off cartridge top, cut nozzle to required size, attach the nozzle to the cartridge. Extrude the sealant firmly against the joint surfaces to ensure complete contact.

Tool the sealant into the joint to compact and achieve a good surface finish. Tool within 10 minutes after sealant is applied. It is recommended to use masking tape on each side to the joint to maintain clean and uniform joint sides. Remove the masking tape directly after tooling the sealant.

### PACKING & COVERAGE

**Classic Acryseal** is available in 500gm, 1kg container and 300 gm cartridges.

1 kg will cover approx 12 to 14 sqm by 5mm depth and 5mm width

### TYPICAL PROPERTIES

Movement accommodation factor:	10%
UV resistance:	Excellent
Sag resistance:	Excellent
Service temperature:	-5 - 60°C
Application temperature:	10 - 50°C
Curing rate:	2 mm / day @ 20°C



PRIMADON CONSTRUCTION PRODUCTS PVT. LTD.

F-C2, Sri Sai Raj Apartments, Indian Airlines Colony, Trimulgherry,  
Secunderabad - 500015, AP, India.

