



# CLASSIC COAT WB-481

## Water Based Epoxy Coating

### **PRODUCT:**

**Classic Coat WB-481** is a two part, water based, epoxy coating, available in different colours. **Classic Coat WB-481** coating provides a dustproof cleanable durable sealing coat on cement and concrete surfaces.

### **DESCRIPTION**

**Classic Coat WB-481** Protective Coating is water based epoxy system which comes in prepacked quantities. The cured film is extremely tough and has a smooth, hard surface. This coating is non toxic in nature.

**Classic Coat WB-481** Protective Coating has excellent adhesion to concrete and cementitious surfaces, outstanding chemical resistance and is unaffected by oil, grease, petrol, etc.

### **ADVANTAGES:**

- \* Resistant to a wide range of Chemicals and Acids.
- \* Hygienic and easily cleaned
- \* Resistant to oil, grease etc.
- \* Excellent adhesion to most.
- \* Easy to apply.
- \* Resistant to fungal attack.

### **PACK & COVERAGE**

1Kg and 5 kg pack. 1 kg pack will cover an area of approximately 3 to 4 Sq.mt for recommended two coats. This will give an overall dry film thickness of 200 microns.

### **PROPERTIES**

Colour	Any color
Pot life (at 30°C)	30 mins.
Curing time (at 30°C)	1 day for light foot traffic 7 days for full chemical resistance

### **WHERE TO USE:**

- \* Water Tanks and Sump
- \* Retaining Walls
- \* Basements and Underground
- \* Terrace and Slope roofs
- \* Sunken Slab
- \* Roof gardening

## **INSTRUCTIONS FOR APPLYING CLASSIC COAT WB-481**

### **1. Surface Preparation:**

Surfaces should be sound, level and free of grease, oil and all loose deposits. Vacuum grit blasting or mechanical scabbing techniques are recommended to ensure optimum adhesion.

#### **Mixing**

Taking care to ensure that the bottom and sides are thoroughly scrapped, transfer the entire contents of the **Classic Coat WB-481** Hardener and **Classic Coat WB-481** Resin into a mixing bucket and using a jiffy-type mixer attached to a slow-running electric drill, mix for approximately two minutes.

#### **Application**

Once mixing is complete, transfer the mixed **Classic Coat WB-481** to roller tray and using a medium-pile simulated sheepskin roller, apply it evenly over the surface.

#### **Cleaning**

Equipment should be cleaned with water immediately after use.

#### **Shelf Life**

Shelf life is 6 months when stored in manufacturer's undamaged sealed containers under dry conditions, and out of direct sun light at temperatures between 5 - 30°C.

### **OUR RANGE INCLUDES**

- **Admixture**
- **Waterproofing**
- **Sealants & Protective Coating**
- **Repairs, Adhesives and Surface Treatment**
- **Industrial Grout & Flooring**
- **Epoxy Products**

### **ECO FRIENDLY & SPECIAL PRODUCTS**

- **Liquid Granites**
- **Geo Polymer based Eco Friendly Products**



PRIMADON CONSTRUCTION PRODUCTS PVT. LTD.  
F-C2, Sri Sai Raj Apartments, Indian Airlines Colony, Trimulgherry,  
Secunderabad - 500015, AP, India.